

# ALPHA™ Big Dot Specifications

Sizes	Big Dot
<b>Case Dimensions (With Power Supply)</b>	49.0" Length x 6.25" Height x 4.25" Depth (124.5 cm L x 16.0 cm H x 11.0 cm D)
<b>Weight</b>	12.25 lbs. (5.6 kg.)
<b>Display Dimensions</b>	45.6" Length x 4.0 " Height (115.8 cm L x 10.16 cm H)
<b>Display Array</b>	80 x 7 pixels
<b>Characters Displayed</b>	14 Minimum/Typical 27 Condensed Rotate
<b>Display Memory</b>	28,000 characters

<b>Pixel Size (Diameter):</b>	.35" (.89 cm)	<b>Serial Computer Interface:</b>	RS232 and RS485 (multi-drop networking for up to 255 displays <i>Options</i> - Ethernet LAN interface - Communications Protocol
<b>Pixel (LED) Color:</b>	8 bright colors and 3 rainbow effects	<b>Keyboard:</b>	Handheld, IR remote operated.
<b>Center-to-Center Pixel Spacing (Pitch):</b>	.57" (1.44 cm)	<b>Software Packages:</b>	AlphaNET <i>plus</i> Windows™
<b>Character Size (One-line format)</b>	4.0" (10.1 cm)	<b>Power Cord Length:</b>	US: 10' ft. (3m)
<b>Character Set:</b>	International Character Set, Block (sans serif), decorative (serif), upper/lower case, slim, wide,	<b>Power:</b>	120VAC or 230 VAC
<b>Memory Retention:</b>	2 weeks typical	<b>Case Material:</b>	ABS high impact plastic
<b>Message Capacity:</b>	80 different messages can be stored and displayed	<b>Limited Warranty:</b>	One-year parts and labor, USA factory servicing
<b>Message Operating Modes:</b>	-26 consisting of: Automode™, Hold, Roll (6 directions), Rotate, Sparkle-on, Twinkle, Interlock, Spray-On, Switch, Wipe (6 directions), Starburst, Flash, Snow, Scroll, Condensed Rotate -Continuous message entry with automatic centering in any mode -User programmable logos and graphics -Five hold speeds	<b>Agency Approvals:</b>	- ETL conforms to EN 60950 IEC950 standards  -FCC Part 15 Class A -CE Marked
<b>Built-in Animations:</b>	Cherry Bomb Exploding, Don't Drink and Drive, Fireworks, Slot Machine, No Smoking, Running Animal, Moving Auto, Welcome (script) and Thank You (script)	<b>Operating Temperature:</b>	32F° to 120F° ; 0° C- 49° C
<b>Real-Time Clock:</b>	Day and time, 12 or 24 hour format, maintains accurate time without power for up to 30 days typical	<b>Humidity Range:</b>	0% to 95% non-condensing
		<b>Mounting:</b>	Hardware to accommodate ceiling or wall mounting.

Salecaster® Displays Corporation Since 1950!

[www.salecaster.com](http://www.salecaster.com)

800 346-4474